

## General Description



EU38 is a 35micron, 38gsm highly breathable, transparent polyurethane film on a filmic carrier with a long history of use in medical applications

Typical Property	Typical Value
Thickness (Micron)	35
Weight (g/m <sup>2</sup> )	38
MVTR, upright (g/m <sup>2</sup> per 24hrs @37°C)	2900
MVTR, inverted (g/m <sup>2</sup> per 24hrs @37°C)	20000
Tensile Strength MD (gf/cm)	800
Tensile Strength TD (gf/cm)	800
Nominal Length at max width (lm)	1000
Minimum Width (mm)	50
Maximum Width (mm)	1300
Carrier	73 gsm release coated filmic carrier
Liner	n/a
Adhesive	n/a
Stripping Load (Release) (gf/cm)	1
Elongation at break, MD (%)	700
Elongation at break, TD (%)	700

Product Information revised 7th March 2018

All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.

**SWM INTL**

Broad Lane • Gilberdyke • East Yorkshire • HU15 2TD  
+44 (0) 1430 440757 • [ams@swmintl.com](mailto:ams@swmintl.com) • <http://swm.indicoll.xyz>