

AU25

General Description



Breathable transparent medical grade aliphatic polyether polyurethane/urethane/tpu film on paper carrier

Typical Property	Typical Value
Thickness (Micron)	23
Weight (g/m ²)	25
MVTR, upright (g/m ² per 24hrs @37°C)	1000
Tensile Strength MD (gf/cm)	800
Tensile Strength TD (gf/cm)	800
Nominal Length at max width (lm)	1000
Minimum Width (mm)	50
Maximum Width (mm)	1280
Carrier	100 gsm release coated paper
Stripping Load (Release) (gf/cm)	1.5
Elongation at break, MD (%)	400
Elongation at break, TD (%)	400
Other Information	The product is intended for use in any application where it is important that the film does not discolour when gamma sterilised.

Product Information revised 27th April 2015

All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.

SWM INTL

Broad Lane • Gilberdyke • East Yorkshire • HU15 2TD
+44 (0) 1430 440757 • ams@swmintl.com • <https://productfinder.swmintl.com>