

General Description



- Key Features:**
- Breathable • Highly conformable • Bacterial barrier • Matt surface • Excellent keying to adhesives
 - Processing**
 - This product is suitable for use where the paper carrier is disposed of during processing. It may also be suitable for applications where the carrier remains in place as part of a dressing delivery system.
 - Applications**
 - Backings for hydrocolloids • First Aid dressings • Medical applications

Typical Property	Typical Value
Thickness (Micron)	28
Weight (g/m ²)	30
MVTR, upright (g/m ² per 24hrs @37°C)	1400
Tensile Strength MD (gf/cm)	1100
Stripping Load (Release) (gf/cm)	2.5
Nominal Length at max width (lm)	1000
Minimum Width (mm)	50
Maximum Width (mm)	1300
Carrier	100gsm single sided release coated paper
Adhesive	n/a
Elongation at break, MD (%)	650
Tensile Strength TD (gf/cm)	1000
Elongation at break, TD (%)	650

Product Information revised 7th March 2018

All statements, product characteristics, and performance data contained herein are believed to be reliable based on observation and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.

SWM INTL

Broad Lane • Gilberdyke • East Yorkshire • HU15 2TD
+44 (0) 1430 440757 • ams@swmintl.com • <https://productfinder.swmintl.com>