

**General Description**



Product Data Sheet – EU29  
Film

Description

- A colourless polyurethane film supplied on a single-sided, release coated paper.

Key Features

- Breathable
- Film is highly conformable
- Bacterial barrier

Processing

- This product is suitable for use where the paper carrier is disposed of during the adhesive coating or conversion process.

Coating or conversion process.

- This product is also suitable for applications where the carrier remains in place as part of a dressing delivery system.

Applications

- Backings for hydrocolloids
- First Aid dressings
- Other medical applications

Typical Property	Typical Value
Thickness (Micron)	27
Weight (g/m <sup>2</sup> )	30
MVTR, upright (g/m <sup>2</sup> per 24hrs @37°C)	1300
Tensile Strength MD (gf/cm)	800
Tensile Strength TD (gf/cm)	800
Nominal Length at max width (lm)	1000
Minimum Width (mm)	50
Maximum Width (mm)	1000
Carrier	120gsm single sided polycoated release paper
Adhesive	n/a

Product Information revised 7th March 2018

All statements, product characteristics, and performance data contained herein are believed to be true and based on laboratory and testing, but no representations, guarantees, or warranties of any kind are made as to accuracy, suitability for particular applications, or the results to be obtained. Nothing contained herein is to be considered to be permission or a recommendation to use any proprietary process or technology without permission of the owner. No warranty of any kind, expressed or implied, is made or intended.

